



New **SPC**
Generation
Flooring

ORIGINALS 
COLLECTIONS
Technical Data Sheet

PRODUCT SPECIFICATION

DECOR	DIMENSIONS	EDGE	SURFACE	CLICK
<p>PLANK</p>	228 X 1220	MICRO BEVEL	EIR	<p>Warranty(Year)</p> <p>20</p>
	Package(m ²) 9 x = 2.503 m ² = 20.20 kg	Palette (m ²) 64 x = 160.220 m ² = 1.292.80 kg	Container(20') 20 x = 3.204.40 m ² = 25.856.00 kg	
<p>HERRINGBONE</p>	150 X 610	MICRO BEVEL	EIR	<p>Warranty(Year)</p> <p>20</p>
	Package(m ²) 16 x = 1.460 m ² = 11,71 kg	Palette (m ²) 108 x = 158.110 m ² = 1.264.90 kg	Container(20') 20 x = 3.162.24 m ² = 25.297.92 kg	

TECNICAL SPECIFICATION

	ICON	STANDARTS	SPECIFICATIONS
Surface treatment (UV)			Yes
Underlay		IXPE	1 mm
Total thickness		ISO24337	5 mm
Wear layer thickness		EN429	0.5 mm
Total weight		EN ISO 23997	8.00- kgs/sqm
Dimensional stability		TS EN ISO 23999	Class 34
Performance classification		23.3443	
Residual indentation after static load		TS EN ISO 24343-1:2007	0.01 mm
Anti-slip resistance		EN 13893	DS
Electrostatic behavior		1815:2016	Anti static floor covering
Floor heating system		Suitable	Max.27 ⁰
Antibacterial		ISO 22196	Antibacterial
Pet-friendly			Pass
Phthalate analysis		Inhouse Method	Phatalete free
Formaldehyde emissions		EN 717-1:2004	E1
Fire behavior		EN13501-1 EN 9239-1:2010	BFL-S1
Reaction to fire		EN 11925-2:2020	Bs-d0
Thermal resistance		EN 12667	0.296 W(m.K)
Matte Degree			2-4 ⁰
VOC emissions		FloorScore CE	Certified
Impact Sound Transmission		ASTM E492-09:2016 - ASTM E989-18	IIC=75dB
Airborne sound transmission loss		ASTM E413-16	R _w +C=75dB - STC = 73dB



ORIGINALS
COLLECTIONS