

CERTIFICATE

for

TÜV PROFiCERT-product Interior PREMIUM

The following product/product group particularly fulfills the criteria V2.0 of the TÜV PROFiCERT-product Interior certification. This certificate does not acquit the producer of his responsibility to comply with all legal requirements and product properties.



MEHR AUS HOLZ.


EGGER Holzwerkstoffe Wismar GmbH & Co. KG
Am Haffeld 1
D-23970 Wismar
Germany

Egger Laminate floor covering UC 31 - 33

Result of quality testing: General requirements and requirements for the levels of use 31 - 33 acc. to EN 13329:2016 are fulfilled

Result of the emission testing: TÜV PROFiCERT-product Interior PREMIUM fulfilled

Thus, the results comply with the emission thresholds of

√	AgBB 2024	√	BREEAM Exemplary Level	√	Austrian Ecolabel UZ 07
√		√	Finnish M1-classification (without odour / ammonia)	√	DE-UZ 176 (Blue Angel)
√	Belgian VOC-regulation	√	MVVTB Annex 8 / ABG	√	CAM Italy construction products
√	LEED v4 (outside North America)	√	QNG		

Certificate registration No. **70 720 6151-1**

Certificate valid from 2024-11-06 to **2027-11-05**

Audit report No. 2117289/2024/1

First certification 2018-11-06



Dr. M. Pawke

Darmstadt, 2024-10-30
Certification body of TÜV Hessen
– Head of Certification body –

ANNEX

This article / this group is characterized by the following features (all data $\pm 10\%$):

Utilisation classes (UC):	A) 31; B) 32; C) 33
Wear layer:	AC3 (A); AC4 (B); AC5 (C)
Decor layer:	Decorative paper impregnated with melamine resin (A, B, C)
Carrier layer:	HDF, thickness 6 – 12 mm, average density 900 kg/m ³ (A, B, C)
Back layer:	Kraft paper impregnated with melamine resin (A, B, C)
V-joint:	Without / 4-sided (A) Without / 2- / 4- / 5-sided (= middle joint) (B, C)
Sound insulation:	Without sound insulation
Total thickness: (Without sound insulation)	6.0 – 8.0 mm (A) 7.0 – 12.0 mm (B) 8.0 – 12.0 mm (C)
Area weight: (Without sound insulation)	5.6 – 7.3 kg/m ² (A) 6.3 – 11.0 kg/m ² (B) 7.3 – 11.0 kg/m ² (C)

and comprises the following articles:

Utilisation class 31 (A)
EGGER NatureSense
EGGER Laminate Flooring
EGGER Basic
EGGER Home
EGGER Pro

Utilisation class 32 (B)
EGGER NatureSense
EGGER NatureSense Aqua
EGGER Laminate Flooring
EGGER Home
EGGER Pro

Utilisation class 33 (C)
EGGER NatureSense
EGGER NatureSense Aqua
EGGER Laminate Flooring
EGGER Home
EGGER Pro

TÜV PROFICERT-product Interior PREMIUM

Certificate registration No. **70 720 6151-1**

Certificate valid from 2024-11-06 to **2027-11-05**



Dr. M. Pawke

Darmstadt, 2024-10-30
Certification body of TÜV Hessen
– Head of Certification body –

ANNEX

This article / this group is characterized by the following features (all data $\pm 10\%$):

Utilisation classes (UC):	A) 32; B) 33
Wear layer:	AC4 (A); AC5 (B)
Decor layer:	Decorative paper impregnated with melamine resin (A, B)
Carrier layer:	HDF, thickness 8 & 12 mm, average density 920 kg/m ³ (A, B)
Back layer:	Kraft paper impregnated with melamine resin (A, B)
V-joint:	4-sided / 5-sided (= middle joint) (A) 4-sided (B)
Sound insulation:	Without sound insulation
Total thickness:	8.0 & 12.0 mm (A) 8.0 mm (B)
Area weight:	6.0 - 7.3 kg/m ² (A, B)

and comprises the following articles:

Utilisation class 32 (A)

EGGER NatureSense Aqua+
EGGER Home Laminate Flooring Aqua+
EGGER Pro Laminate Flooring Aqua+

Utilisation class 33 (B)

EGGER NatureSense Aqua+
EGGER Pro Laminate Flooring Aqua+

TÜV PROFICERT-product Interior PREMIUM

Certificate registration No. **70 720 6151-1**

Certificate valid from 2024-11-06 to **2027-11-05**



Dr. M. Pawide

Darmstadt, 2024-10-30
Certification body of TÜV Hessen
– Head of Certification body –